Pro Single Tower

178 x 74 cm | 4.2 / 6.2 m | 2M





PRO





Specifications

Working Height: 6.2 m Standing Height: 4.2 m Scaffolding Class: 3.0 Length: 178 cm Weight: 103.96 kg

Width: 74 cm
Material: Aluminium, Veneer

Colour: Grey

Castor Size: Ø12,5 cm Load Capacity: 200 kg/m² Certification: EN1004

Jumbo Brand: PRO SCAFFOLDS

| Product no. | DBNumber | EAN Code | Jumbo Brand | Warranty | Net Weight |
|-------------|----------|----------|---------------|----------|------------|
| 7978-4-T | 2271133 | | PRO SCAFFOLDS | 10 years | 103.96 kg |

Description

The JUMBO Scaffolding Pro Single Tower is a professional and flexible aluminium scaffold, specifically designed for 2 m planking. This scaffold is ideal for professional craftsmen who require stability and flexibility in their daily tasks.

2 m planking: Maximum height to the first platform is 3.40 m, and the distance between subsequent platforms is 2.25 m, making it suitable for tasks that require precise working levels.

The scaffold is constructed with fully welded joints on all frames, ensuring additional strength and stability during use. Diagonal braces and guardrails are equipped with high-impact, fully cast claws, which also feature fully welded joints, providing extra robustness.

The platforms are made from waterproof, non-slip Finnish birch plywood, mounted in strong aluminium frames. The platforms feature staggered hooks, allowing for extension without displacement, and are secured with a patented storm lock underneath, providing extra safety.

As standard, JUMBO Scaffolding comes with Ø125 mm castors with brakes. The castors are coated with polyurethane, ensuri

Detail Images



Non-slip platforms equipped with staggered hooks, which makes lengthwise extention without displacement possible



Placed at each end under the platform, the patented storm locks are used to secure the platform to the scaffold



Fully welded frames




High-impact self-locking claws on all horizontal braces and diagonals (tube dimensions: Ø50x2mm). The claws are cast solid quality with fully welded joints.

The set consists of

| 2 STK | 12074100 | Frame 1 m | 2 STK | 12074101 | Guardrail frame narrow 1 m |
|---------------|--------------|-----------------------------|-------|----------|--|
| 3 STK | 12074200 | Frame 2 m | 2 STK | 1001781 | Platform w/hatch |
| 9 STK | 1101780 | Horizontal brace | 4 STK | 1102500 | Horizontal brace / diagonal |
| 1 STK | katalog/avis | JUMBO 2024 product brochure | 1 STK | | Assembly instructions Rolling scaffold |
| 8 STK | FLB-1 | Toeboard clip | 4 STK | 1400125 | Castor w/brakes |
| 10 STK | 1600100 | Safety clips | | <u>-</u> | • |

Spareparts



Accessories




Exchanges castors

1400204 7782766



Frame 2 m 12074200 7782808



Extensions set for single towers

s-1178 5929674



Platform Sets w/Railing 101781sk 5929707



Toeboard Sets

1620178s 5741563



Outrigger 1410150

7782741