# **Pro Single Towers**

178 x 74 cm | 3.2 / 5.2 m





PRO





Working Height: 5.2 m Standing Height: 3.2 m Length: 178 cm

Weight: 70.24 kg Width: 74 cm

Material: Aluminium, Veneer

Colour: Grey

Castor Size: Ø12,5 cm Load Capacity: 200 kg/m² Certification: EN1004

Jumbo Brand: PRO SCAFFOLDS

8	5

Product no.	DBNumber	EAN Code	Jumbo Brand	Warranty	Net Weight
7978	5741556		PRO SCAFFOLDS	10 years	70.24 kg

## **Description**

JUMBO Scaffolding Pro Single Towers is a versatile aluminium scaffold in professional craftsman quality, ideal for both small and large tasks. This set is specifically designed for 2 m and 4 m planking, offering flexibility in platform heights, making it suitable for various work applications.

2 m planking: Max. height to the first platform is 3.40 m, and max. 2.25 m between subsequent platforms. 4 m planking: Max. height to the first platform is 4.40 m, and max. 4.00 m between subsequent platforms. The scaffold is built with fully welded joints on all frames, ensuring enhanced strength and stability. The diagonal braces and guardrails are fitted with high-impact, solid claws that are designed to withstand heavy loads and daily use.

The platforms are made from waterproof, non-slip Finnish birch plywood, mounted in strong aluminium frames, providing a stable and durable work surface. The staggered hooks on the platforms allow for lengthwise extension without displacement. Additionally, a patented storm lock underneath the platforms secures them against movement in windy conditions and fits all types of scaffolding.

As standard, JUMBO Scaffolding is equipped with extra-sturdy Ø125 mm castors with brakes. These castors feature a polyure

# **Detail Images**



Non-slip platforms equipped with staggered hooks, which makes lengthwise extention without displacement possible



Placed at each end under the platform, the patented storm locks are used to secure the platform to the scaffold



Fully welded frames



High-impact self-locking claws on all horizontal braces and diagonals (tube dimensions: Ø50x2mm). The claws are cast solid quality with fully welded joints.

#### The set consists of

2 STK	12074200
2 STK	12074101
3 STK	1102500
4 STK	1400125
4 OTI	EL D 4

4 STK | FLB-1

1 STK | katalog/avis

Frame 2 m Guardrail frame narrow 1 m Horizontal brace / diagonal

Castor w/brakes Toeboard clip

JUMBO 2024 product brochure

2 STK | 12074100 5 STK | 1101780 1 STK | 1001781 8 STK | 1600100 1 STK | mont-RULLE

Frame 1 m
Horizontal brace
Platform w/hatch
Safety clips
Assembly instructions Rolling scaffold

## **Spareparts**



ALU Locking mechanism 1600300



Plywood for platforms w/o hatch 7501780



Hook 1690050



Storm lock 1003050231



End piece 100305023



Screw 5.5x25 skrue



Pop rivet Popnitte6,4x22



Pop rivet Popnitte6,4x12



Single Coupler 18SFS216 5189340



Bushing 1400210NY



Top plug for screwjack 1400211NY

#### **Accessories**



Exchanges castors 1400204 7782766



Frame 2 m 12074200 7782808



Extensions set for single towers s-1178 5929674



Platform Sets w/Railing 101781sk 5929707



Toeboard Sets 1620178s 5741563



Outrigger 1410150 7782741