# **Pro Double Towers AGR**

250 x 135 cm | 6.2 / 8.2 m





PRO





Working Height: 8.2 m Standing Height: 6.2 m Scaffolding Class: 3.0

Length: 250 Weight: 247.08 kg Width: 135 cm

Material: Aluminium, Plastic, Veneer

Colour: Grey

Castor Size: Ø12,5 cm Load Capacity: 200 kg/m<sup>2</sup> Certification: EN1004

Jumbo Brand: PRO SCAFFOLDS



Product no.	DBNumber	EAN Code	Jumbo Brand	Warranty	Net Weight
9900-6-A	2335426		PRO SCAFFOLDS	10 years	247.08 kg

### **Description**

The JUMBO Scaffolding Pro Double Towers AGR is a professional-grade aluminium scaffold, perfect for craftsmen who require high quality and flexibility in their work. This set is specially configured for 2 m planking, with a maximum height to the first platform of 3.40 m and a distance of 2.25 m between subsequent platforms.

The scaffold is equipped with AGR (Advanced Guardrail) guardrails featuring built-in diagonal bracing, which adds extra stability and safety during use. The AGR guardrails are made with high-impact claws from fibreglass-reinforced plastic, ensuring a strong and reliable structure.

2m planking: Max. height to the first platform is 3.40 m and max. 2.25 m between following platforms. Materials: The frames are made of aluminium with fully welded joints for added strength and stability. The scaffold decks are made from waterproof, non-slip Finnish birch plywood, mounted in strong aluminium frames. The staggered hooks on the decks allow for lengthwise extension without displacement. Additionally, the platforms are secured with a patented storm lock underneath, providing safety during windy conditions.

JUMBO Scaffolding is supplied as standard with extra sturdy Ø125 mm castors with brakes. The castors feature a durable pol

## **Detail Images**



Non-slip platforms equipped with staggered hooks, which makes lengthwise extention without displacement possible



Placed at each end under the platform, the patented storm locks are used to secure the platform to the scaffold



Fully welded frames



Impact-resistant Fibreglass Reinforced Plastic Claws

#### The set consists of

4 STK	1400125 12135100
2 STK	12135100
2 STK	1102504
6 STK	1102500-AGR
3 STK	1002500
<b>12</b> STK	FLB-1


Castor w/brakes
Frame 1 m
Diagonals
Railing w/diagonals
Platform w/o hatch
Toeboard clip

JUMBO 2024 product brochure

<b>5</b> STK	12135200
2 STK	12135101
1 STK	1102500
3 STK	1002501
<b>14</b> STK	1600100
1 STK	mont-RULLE


Frame 2 m
Guardrail frame wide
Horizontal brace / diagonal
Platform w/hatch
Safety clips
Assembly instructions Rolling
scaffold

### **Spareparts**



1 STK katalog/avis

### **Accessories**



Railing w/diagonals 1102500-AGR 2335720



Toeboard Sets 1620178s 5741563



Exchanges castors 1400204

7782766



Platform Sets w/Railing 102501BK 7782725



Frame 1 m 12135100 7782790



Frame 1 m 12074100 7782816



Frame 0,5 m 12074050 5929662



Outrigger 1410250 7782758



Extensions set for double towers

b-1 7782709