Combiflex Universal Scaffold

4 x 6 m



Specifications

Working Height: 6 m Standing Height: 4 m Scaffolding Class: 3.0 Weight: 384.9 kg Material: Steel Colour: Grey Load Capacity: 200 kg/m² Jumbo Brand: PRO SCAFFOLDS

Product no.	DBNumber	EAN Code	Jumbo Brand	Warranty	Net Weight
214006C	1609765		PRO SCAFFOLDS	3 years	384.9 kg

Description

The JUMBO Combiflex Universal Scaffold is a flexible and robust scaffolding system designed to meet even the most demanding construction needs. The scaffold is made from hot-dip galvanised high-quality steel, ensuring both high strength and low weight, and providing resistance to corrosion. With built-in diagonal bracing in the railing and an innovative cup/ wedge-lock joint system, it is quick and easy to assemble and disassemble. This universal scaffold can be constructed at any angle, 360° around, with up to 8 components at each node, offering maximum flexibility on the construction site.

The JUMBO Combiflex is manufactured in accordance with EN12810 standards, ensuring high quality and safety.

Detail Images



Cup/wedge assembly





Can be build in any angle

The set consists of

6 STK 21JCF200S 9 STK 21JCF70H 6 STK 21JCF300RR 2 STK 1003001 6 STK 21JCF740F 10 STK 21JCF-F 6 STK 1591010

6 STK 1591010



ALU Locking mechanism 1600300



Plywood for platforms w/o hatch 7501780

Combiflex Standard

Combiflex Railings


Combiflex Base Jack

Combiflex Toeboard clip

Platform w/hatch

Eye Screws

Combiflex Horisontal Braces



21JCF300S

6 STK

Combiflex Standard Combiflex Railings Platform w/o hatch Scaffold Ladders Lynch pin Tie rod w/clamp Rawplugs




HOOK 1690050



Storm lock 1003050231



Screw 5,5x25 skrue



Pop rivet Popnitte6,4x22



Pop rivet Popnitte6,4x12



Single Coupler 18SFS216 5189340

End piece

100305023



1400210NY



Top plug for screwjack 1400211NY



ALU Locking mechanism 1600300

Accessories

