


Pro Single Towers

305 x 74 cm | 3.2 / 5.2 m



EN1004

PRO

10 YEAR WARRANTY



Specifications

- Working Height: 5.2 m
- Standing Height: 3.2 m
- Scaffolding Class: 3.0
- Load Capacity: 200 kg/m²
- Length: 305 cm
- Width: 74 cm
- Weight: 88.44 kg
- Material: Aluminium, Veneer
- Colour: Grey
- Castor Size: Ø12,5 cm
- Certification: EN1004
- Jumbo Brand: PRO SCAFFOLDS

| Product no. | DBNumber | EAN Code | Jumbo Brand | Warranty | Net Weight |
|-------------|----------|----------|---------------|----------|------------|
| 79305 | 5741551 | | PRO SCAFFOLDS | 10 years | 88.44 kg |

Description

JUMBO Scaffolding Pro Single Towers is a versatile aluminium scaffold in professional craftsman quality, ideal for both small and large tasks. This set is specifically designed for 2 m and 4 m planking, offering flexibility in platform heights, making it suitable for various work applications.

- 2 m planking: Max. height to the first platform is 3.40 m, and max. 2.25 m between subsequent platforms.
- 4 m planking: Max. height to the first platform is 4.40 m, and max. 4.00 m between subsequent platforms.
- The scaffold is built with fully welded joints on all frames, ensuring enhanced strength and stability. The diagonal braces and guardrails are fitted with high-impact, solid claws that are designed to withstand heavy loads and daily use.


The platforms are made from waterproof, non-slip Finnish birch plywood, mounted in strong aluminium frames, providing a stable and durable work surface. The staggered hooks on the platforms allow for lengthwise extension without displacement. Additionally, a patented storm lock underneath the platforms secures them against movement in windy conditions and fits all types of scaffolding.

As standard, JUMBO Scaffolding is equipped with extra-sturdy Ø125 mm castors with brakes. These castors feature a polyure

Detail Images



Non-slip platforms equipped with staggered hooks, which makes lengthwise extension without displacement possible



Placed at each end under the platform, the patented storm locks are used to secure the platform to the scaffold



Fully welded frames



High-impact self-locking claws on all horizontal braces and diagonals (tube dimensions: Ø50x2mm). The claws are cast solid quality with fully welded joints.

The set consists of

| | | |
|-------|--------------|-----------------------------|
| 2 STK | 12074200 | Frame 2 m |
| 2 STK | 12074101 | Guardrail frame narrow 1 m |
| 3 STK | 1103510 | Diagonals |
| 4 STK | 1400125 | Castor w/brakes |
| 4 STK | FLB-1 | Toeboard clip |
| 1 STK | katalog/avis | JUMBO 2024 product brochure |

| | | |
|-------|------------|--|
| 2 STK | 12074100 | Frame 1 m |
| 5 STK | 1103050 | Horizontal brace / diagonal |
| 1 STK | 1003051 | Platform w/hatch |
| 8 STK | 1600100 | Safety clips |
| 1 STK | mont-RULLE | Assembly instructions Rolling scaffold |

Spareparts



ALU Locking mechanism
1600300



Plywood for platforms w/o hatch
7501780



Hook
1690050



Storm lock
1003050231



End piece
100305023



Screw
5,5x25 skrue



Pop rivet
Popnitte6,4x22



Pop rivet
Popnitte6,4x12



Single Coupler
18SFS216
5189340



Bushing
1400210NY



Top plug for screwjack
1400211NY

Accessories



Exchanges castors
1400204
7782766



Frame 2 m
12074200
7782808



Extensions set for single
towers
s-1305
5929675



Platform Sets w/Railing
103051sk
5741559



Toeboard Sets
1620305s
5741565



Outrigger
1410150
7782741