Pro Single Towers AGR

178 x 74 cm | 8.2 / 10.2 m





PRO





Working Height: 10.2 m Standing Height: 8.2 m Scaffolding Class: 3.0 Load Capacity: 200 kg/m²

Length: 178 cm Width: 74 cm Weight: 203.3 kg

Material: Aluminium, Veneer

Colour: Grey

Castor Size: Ø12,5 cm Certification: EN1004

Jumbo Brand: PRO SCAFFOLDS

| · |
|---|

| Product no. | DBNumber | EAN Code | Jumbo Brand | Warranty | Net Weight |
|-------------|----------|----------|---------------|----------|------------|
| 7978-8-A | 2335375 | | PRO SCAFFOLDS | 10 years | 203.3 kg |

Description

The JUMBO Scaffolding Pro Double Towers AGR is the perfect choice for professional craftsmen who require flexibility and stability in their work tasks. The scaffold is specifically designed for 2 m planking, with a maximum height of 3.40 m to the first platform and 2.25 m between subsequent platforms, making it ideal for larger projects.

This scaffold is equipped with the advanced AGR guardrail, featuring built-in diagonal bracing to ensure optimal stability and safety. The claws on the diagonals and guardrails are made from high-impact, fibreglass-reinforced plastic, providing extra durability and strength.

The scaffold platforms are made from waterproof, non-slip Finnish birch plywood, mounted in strong aluminium frames. The staggered hooks on the platforms allow for lengthwise extension without displacement, and the patented storm lock underneath ensures that the platforms stay securely in place under all weather conditions.

As standard, JUMBO Scaffolding comes with Ø125 mm castors with brakes. The castors feature a durable polyurethane coating, making them resistant to solvents and wear. The castors can be replaced with larger Ø200 mm castors with brakes a

Detail Images



Non-slip platforms equipped with staggered hooks, which makes lengthwise extention without displacement possible



Placed at each end under the platform, the patented storm locks are used to secure the platform to the scaffold



Fully welded frames



Impact-resistant Fibreglass Reinforced Plastic Claws

The set consists of

| 4 STK | 1400125 |
|---------------|-------------|
| 2 STK | 12074100 |
| 2 STK | 1101784 |
| 8 STK | 1101780-AGR |
| 18 STK | 1600100 |
| 1 STK | mont-RULLE |
| | |

| Oi |
|--|
| Castor w/brakes |
| Frame 1 m |
| Diagonals |
| Railing w/diagonals |
| Safety clips |
| Assembly instructions Rolling scaffold |

| 7 STK | 12074200 |
|---------------|--------------|
| 2 STK | 12074101 |
| 1 STK | 1101780 |
| 4 STK | 1001781 |
| 16 STK | FLB-1 |
| 1 STK | katalog/avis |
| | 1 |
| | |

| re |
|----|
| re |
| |

Spareparts





Railing w/diagonals 1101780-AGR 2335718



Toeboard Sets 1620178s 5741563



Exchanges castors 1400204

7782766





Frame 2 m 12074200 7782808



Frame 1 m 12074100 7782816



Guardrail frame narrow 1 m 12074101 7782824



Outrigger 1410250 7782758



Extensions set for single towers

s-1178 5929674