

# Pro Single Towers w/mounting Platform

178 x 74 cm | 3.2 / 5.2 m



EN1004 PRO 10 YEAR WARRANTY



## Specifications

Working Height: 5.2 m  
Standing Height: 3.2 m  
Scaffolding Class: 3.0  
Load Capacity: 200 kg/m<sup>2</sup>  
Length: 178 cm  
Width: 74 cm  
Weight: 81.74 kg  
Material: Aluminium, Veneer  
Colour: Grey  
Castor Size: Ø12,5 cm  
Certification: EN1004  
Jumbo Brand: PRO SCAFFOLDS

| Product no. | DBNumber | EAN Code | Jumbo Brand   | Warranty | Net Weight |
|-------------|----------|----------|---------------|----------|------------|
| 7978-M      | 1612984  |          | PRO SCAFFOLDS | 10 years | 81.74 kg   |

## Description

JUMBO Scaffolding Pro Single Towers is a versatile aluminium scaffold in professional craftsman quality, ideal for both small and large tasks. This set is specifically designed for 2 m and 4 m planking, offering flexibility in platform heights, making it suitable for various work applications.

2 m planking: Max. height to the first platform is 3.40 m, and max. 2.25 m between subsequent platforms.

4 m planking: Max. height to the first platform is 4.40 m, and max. 4.00 m between subsequent platforms.

The scaffold is built with fully welded joints on all frames, ensuring enhanced strength and stability. The diagonal braces and guardrails are fitted with high-impact, solid claws that are designed to withstand heavy loads and daily use.


The platforms are made from waterproof, non-slip Finnish birch plywood, mounted in strong aluminium frames, providing a stable and durable work surface. The staggered hooks on the platforms allow for lengthwise extension without displacement. Additionally, a patented storm lock underneath the platforms secures them against movement in windy conditions and fits all types of scaffolding.

As standard, JUMBO Scaffolding is equipped with extra-sturdy Ø125 mm castors with brakes. These castors feature a polyure

## Detail Images



Non-slip platforms equipped with staggered hooks, which makes lengthwise extension without displacement possible



Placed at each end under the platform, the patented storm locks are used to secure the platform to the scaffold



Fully welded frames



High-impact self-locking claws on all horizontal braces and diagonals (tube dimensions: Ø50x2mm). The claws are cast solid quality with fully welded joints.

## The set consists of

|       |              |                             |       |            |  |
|-------|--------------|-----------------------------|-------|------------|--|
| 2 PCS | 12074200     | Frame 2 m                   | 2 PCS | 12074100   | Frame 1 m                              |
| 2 PCS | 12074101     | Guardrail frame narrow 1 m  | 5 PCS | 1101780    | Horizontal brace                       |
| 3 PCS | 1102500      | Horizontal brace / diagonal | 1 PCS | 1001781    | Platform w/hatch                       |
| 4 PCS | 1400125      | Castor w/brakes             | 8 PCS | 1600100    | Safety clips                           |
| 4 PCS | FLB-1        | Toeboard clip               | 1 PCS | mont-RULLE | Assembly instructions Rolling scaffold |
| 1 PCS | katalog/avis | JUMBO 2024 product brochure | 1 PCS | 1001781    | Platform w/hatch                       |

## Spareparts



ALU Locking mechanism  
1600300



Plywood for platforms w/o hatch  
7501780



Hook  
1690050



Storm lock  
1003050231



End piece  
100305023



Screw  
5,5x25 skruer



Pop rivet  
Popnitte6,4x22



Pop rivet  
Popnitte6,4x12



Bushing  
1400210NY



Top plug for screwjack  
1400211NY

## Accessories



Exchanges castors

1400204


7782766



Frame 2 m

12074200

7782808



Extensions set for single towers

s-1178

5929674



Platform Sets w/Railing

101781sk

5929707



Toeboard Sets

1620178s

5741563



Outrigger

1410150

7782741