Pro Double Towers

178 x 135 cm | 7.2 / 9.2 m | 4M

EN1004 PRO 10 YEAR WARRANTY

Specifications

Working Height: 9.2 m
Standing Height: 7.2 m
Scaffolding Class: 3.0
Load Capacity: 200 kg/m²
Length: 178 cm
Width: 135 cm
Weight: 187.86 kg
Material: Aluminium,Veneer
Colour: Grey
Castor Size: Ø12,5 cm
Certification: EN1004
Jumbo Brand: PRO SCAFFOLDS

Product no.	DBNumber	EAN Code	Jumbo Brand	Warranty	Net Weight
9978-7	5348167		PRO SCAFFOLDS	10 years	187.86 kg

Description

The JUMBO Scaffolding Pro Double Towers is a professional-grade aluminium scaffold, specially designed for 4m planking. Built to withstand the rigorous demands of professional craftsmen, it offers durability and flexibility for larger projects.

4m planking: Maximum height to the first platform is 4.40 m, and the distance between subsequent platforms can be up to 4.00 m, making it ideal for taller workspaces and construction projects.
The scaffold is built with fully welded joints on all frames, ensuring maximum strength and stability during use. Diagonal braces and guardrails are fitted with high-impact, fully cast claws, with fully welded joints for added safety and durability.

The platforms are made from waterproof, non-slip Finnish birch plywood, mounted in sturdy aluminium frames. The staggered hooks on the platforms allow for lengthwise extension without displacement. Additionally, the platforms are secured with a patented storm lock underneath, which prevents accidental movement and is compatible with all types of scaffolding.

As standard, JUMBO Scaffolding is supplied with extra-sturdy Ø125 mm castors with brakes, ensuring stability during movement and setup. The castors are coated with polyurethane, providing high wear resistance and solvent resistance. There

JUMBO takes no responsibility for typing errors, image errors, sold out items and price changes without further notice

Detail Images

Non-slip platforms equipped with staggered hooks, which makes lengthwise extention without displacement possible

Placed at each end under the platform, the patented storm locks are used to secure the platform to the scaffold

Fully welded frames

High-impact self-locking claws on all horizontal braces and diagonals (tube dimensions: Ø50x2mm). The claws are cast solid quality with fully welded joints.

The set consists of

4 PCS	1400125	Castor w/brakes
2 PCS	12135100	Frame 1 m
7 PCS	1102500	Horizontal brace / diagonal
2 PCS	1001781	Platform w/hatch
16 PCS	1600100	Safety clips
1 PCS	mont-RULLE	Assembly instructions Rolling scaffold
6 PCS	12135200	Frame 2 m
2 PCS	12135101	Guardrail frame wide
9 PCS	1101780	Horizontal brace
2 PCS	1001780	Platform w/o hatch
8 PCS	FLB-1	Toeboard clip
1 PCS	katalog/avis	JUMBO 2024 product brochure

Spareparts

ALU Locking mechanism
1600300

Plywood for platforms w/o hatch
7501780

Hook
1690050

Storm lock
1003050231

End piece
100305023

Screw
5,5x25 skrue

Pop rivet
Popnitte6,4x22

Pop rivet
Popnitte6,4x12

Bushing
1400210NY

Top plug for screwjack
1400211NY

Accessories

JUMBO takes no responsibility for typing errors, image errors, sold out items and price changes without further notice

Frame 2 m
12135200
7782782

Extensions set for double towers
b-1178
5929672

Platform Sets w/Railing
101781bk
5929706

Toeboard Sets
1620178b
5741567

Exchanges castors
1400204
7782766

Outrigger
1410250
7782758

JUMBO takes no responsibility for typing errors, image errors, sold out items and price changes without further notice