


# Pro Single Towers

178 x 74 cm | 8.2 / 10.2 m | 4M



## Specifications

Working Height: 10.2 m  
Standing Height: 8.2 m  
Scaffolding Class: 3.0  
Length: 178 cm  
Width: 74 cm  
Weight: 149.16 kg  
Material: Aluminium, Veneer  
Colour: Grey  
Castor Size: Ø12,5 cm  
Certification: EN1004  
Jumbo Brand: PRO SCAFFOLDS

| Product no. | DBNumber | EAN Code | Jumbo Brand   | Warranty | Net Weight |
|-------------|----------|----------|---------------|----------|------------|
| 7978-8      | 5741560  |          | PRO SCAFFOLDS | 10 years | 149.16 kg  |

## Description

The JUMBO Scaffolding Pro Single Towers is a professional aluminium scaffold, specifically designed for 4 m planking. It is ideal for craftsmen who require a flexible and strong scaffold for larger construction and maintenance tasks.

4 m planking: Maximum height to the first platform is 4.40 m, with a distance of up to 4.00 m between subsequent platforms, making it perfect for working at elevated heights.

The scaffold's frames feature fully welded joints, ensuring additional strength and stability during use. Diagonal braces and guardrails are equipped with high-impact, fully cast claws at each end, providing added durability and robustness. The fully cast claws guarantee that the joints remain strong over time.


The platforms are made from waterproof, non-slip Finnish birch plywood, mounted in strong aluminium frames. The staggered hooks on the platforms allow for lengthwise extension without displacement. Underneath the platforms, a patented storm lock secures the decks, preventing movement during adverse weather conditions.

As standard, JUMBO Scaffolding is supplied with extra sturdy Ø125 mm castors with brakes, ensuring easy and safe mobility.

## Detail Images



Non-slip platforms equipped with staggered hooks, which makes lengthwise extension without displacement possible



Placed at each end under the platform, the patented storm locks are used to secure the platform to the scaffold



Fully welded frames



High-impact self-locking claws on all horizontal braces and diagonals (tube dimensions: Ø50x2mm). The claws are cast solid quality with fully welded joints.

## The set consists of

|        |              |                             |       |            |  |
|--------|--------------|-----------------------------|-------|------------|--|
| 2 PCS  | 1001781      | Platform w/hatch            | 9 PCS | 1101780    | Horizontal brace                       |
| 8 PCS  | 1102500      | Horizontal brace / diagonal | 4 PCS | 1400125    | Castor w/brakes                        |
| 18 PCS | 1600100      | Safety clips                | 2 PCS | 12074100   | Frame 1 m                              |
| 2 PCS  | 12074101     | Guardrail frame narrow 1 m  | 7 PCS | 12074200   | Frame 2 m                              |
| 8 PCS  | FLB-1        | Toeboard clip               | 1 PCS | mont-RULLE | Assembly instructions Rolling scaffold |
| 1 PCS  | katalog/avis | JUMBO 2024 product brochure |       |            |  |

## Spareparts



ALU Locking mechanism  
1600300



Plywood for platforms w/o hatch  
7501780



Hook  
1690050



Storm lock  
1003050231



End piece  
100305023



Screw  
5,5x25 skrue



Pop rivet  
Popnitte6,4x22



Pop rivet  
Popnitte6,4x12



Bushing  
1400210NY



Top plug for screwjack  
1400211NY

## Accessories



Exchanges castors

1400204


7782766



Frame 2 m

12074200

7782808



Extensions set for single towers

s-1178

5929674



Platform Sets w/Railing

101781sk

5929707



Toeboard Sets

1620178s

5741563



Outrigger

1410250

7782758