


Platform ALU

29,5 x 305 cm | Cl. 5



PRO

Specifications

- Scaffolding Class: 5.0
- Load Capacity: 600 kg
- Length: 3.05 m
- Width: 29.5 cm
- Weight: 14.2 kg
- Material: Aluminium,Steel
- Colour: Grey
- Transport Length: 3.113 m
- Transport Height: 0.09 m
- Transport Width: 0.295 m
- Jumbo Brand: PRO SCAFFOLDS



Product no.	DBNumber	EAN Code	Jumbo Brand	Warranty	Net Weight
100AD305H	2056500		PRO SCAFFOLDS	1 years	14.2 kg

Description

JUMBO ALU platform is produced in accordance with EN12810 - Meets ergonomic requirements (15 kg.) For masonry work etc. via dead weight of 6.9 to 14.2 kg. Dimensioned and tested according to scaffolding class 6 (up to and including cc. 250 cm. Length) and scaffolding class 5 (up to and including cc. 305 cm. Length).

Easy and quick replacement of end pieces, via 4 stainless steel bolts with self-locking stainless steel nuts. The half deck is assembled with stainless steel bolts that are both strong and resistant to wind and weather.

The half-tire is produced in an extruded aluminum profile in special alloy that is both strong, torsionally stable and resistant to wind and weather. In the surface, there are pull-ups in the holes - the same pull-up as in our driveway ramps - which makes the tire incredibly strong and non-slip. This minimizes the risk of falls and slippery accidents on the scaffolding.

The storm lock can be unlocked and in from the top of the tire with a 22 mm. scaffolding key, but also with a hand from the underside of the platform

The tire can be stacked in two ways:

Detail Images

The set consists of

PCS | |

Spareparts



Screw
5,5x25 skrue



Pop rivet
Popnitte6,4x22



Pop rivet
Popnitte6,4x12

Accessories

